



**Notes:**

Space Baron General Filter "AC-1" Residential Air Cleaner replacement filters are 5" deep pleated Quality Pleats that are specifically designed to replace other 20" x 24" ducted air products. Space Baron General Filter "AC-1" is available in 3 efficiencies including: MERV 8, MERV 11, and Carbon medias.

**Performance Data - Space Baron General Filter "AC-1"**

Product Code	ASHRAE 52.2 - 1999				Initial Resistance " w.g. @ 1032 cfm	Final Resistance " w.g. @ 1032 cfm
	MERV Value	E1 %	E2 %	E3 %		
SBGF140	8	n/a	n/a	n/a	0.08	.50
SBGF1MQP	11	n/a	n/a	n/a	0.1	.50
SBGF1OB**	8	n/a	n/a	n/a	0.07	.50

**Part Number Guide**

Product Code	Description	Nominal Dimensions	Actual Frame Dimensions w/o Gasketing
SBGF140	Type 40 - MERV 8	20" x 24" x 5"	19.5" x 24" x 4.8"
SBGF1MQP	MQP - MERV 11	20" x 24" x 5"	19.5" x 24" x 4.8"
SBGF1BOB	Odor Ban - MERV 8	20" x 24" x 5"	19.5" x 24" x 4.8"

\*Trade names and company names are used for identification purposes only.

Characteristics	Space Baron General Filter "AC-1"	<p align="center"> <a href="http://FurnaceFilterSuperstore.com">Furnace Filter Superstore.com</a>                      550 Elmwood Park Blvd Ste D                      Harahan, LA 70123  <a href="http://www.furnacefiltersuperstore.com">www.furnacefiltersuperstore.com</a> </p> <p align="center"> <b>Quality Filters Space Baron</b>  <b>General Filter "AC-1" 20" x 24" x 5"</b> </p>						
Filter Media - Particulate	100% synthetic gradient media, electrostatically charged				DR	JJS	Date 28 Sep 07	Dwg No.
**Filter Media - Odor Ban	Fine carbon powder bonded to lofted polyester media	CK	JH	Date 28 Sep 07				
Filter Support Grid	30 gauge galvanized expanded metal grid							
Frame	Moisture resistant 28 point beverage board							
Gasketing	Closed cell urethane foam							
Assembly Technique	Media pack totally bonded to frame							
Max. Temperature	180°F (82°C) continuous service, Peaks 225°F (107°C)							
Max. Humidity	Resistant to 100% R.H.							