



Notes:

Space Baron Honeywell FC100A* Series Residential Air Cleaner replacement filters are 5" deep pleated Quality Pleats that are specifically designed to replace other comparably sized ducted air products. Space Baron Honeywell FC100A* Series is available in 3 efficiencies including: MERV 8, MERV 11, and Carbon medias.

Performance Data - Space Baron Honeywell FC100A Series*

Product Code	ASHRAE 52.2 - 1999				Initial Resistance*w.g.		Final Resistance*w.g.	
	MERV Value	E1 %	E2 %	E3 %	@ 1032 cfm	@ 836 cfm	@ 1032 cfm	@ 836 cfm
					SBHW2940	8	n/a	n/a
SBHW29MQP	11	n/a	n/a	n/a	-	0.1	-	.50
SBHW29OB	8	n/a	n/a	n/a	-	0.07	-	.50
SBHW1140	8	n/a	n/a	n/a	-	0.08	-	.50
SBHW11MQP	11	n/a	n/a	n/a	-	0.1	-	.50
SBHW11OB	8	n/a	n/a	n/a	-	0.07	-	.50
SBHW3740	8	n/a	n/a	n/a	0.08	-	.50	-
SBHW37MQP	11	n/a	n/a	n/a	0.1	-	.50	-
SBHW37OB	8	n/a	n/a	n/a	0.07	-	.50	-

Part Number Guide

Product Code	Description	Nominal Dimensions	Actual Frame Dimensions
SBHW2940	Type 40 - MERV 8	16" x 25" x 5"	15.875" x 24.75" x 4.25"
SBHW1140	Type 40 - MERV 8	20" x 20" x 5"	19.75" x 19.75" x 4.25"
SBHW3740	Type 40 - MERV 8	20" x 25" x 5"	19.75" x 24.75" x 4.25"
SBHW29MQP	MQP - MERV 11	16" x 25" x 5"	15.875" x 24.75" x 4.25"
SBHW11MQP	MQP - MERV 11	20" x 20" x 5"	19.75" x 19.75" x 4.25"
SBHW37MQP	MQP - MERV 11	20" x 25" x 5"	19.75" x 24.75" x 4.25"
SBHW29OB	Odor Ban - MERV 8	16" x 25" x 5"	15.875" x 24.75" x 4.25"
SBHW11OB	Odor Ban - MERV 8	20" x 20" x 5"	19.75" x 19.75" x 4.25"
SBHW37OB	Odor Ban - MERV 8	20" x 25" x 5"	19.75" x 24.75" x 4.25"

*Trade names and company names are used for identification purposes only.

Characteristics	Space Baron Honeywell FC100A* Series	Furnace Filter Superstore 550 Elmwood Park Blvd Ste D Harahan, LA 70123 www.furnacefiltersuperstore.com		
Filter Media - Particulate	100% synthetic gradient media, electrostatically charged	Quality Filters Space Baron Honeywell FC100A* Series		
Filter Media - Odor Ban	Fine carbon powder bonded to lofted polyester media			
Filter Support Grid	30 gauge galvanized expanded metal grid			
Frame	Moisture resistant 28 point beverage board			
Assembly Technique	Media pack totally bonded to frame			
Max. Temperature	180°F (82°C) continuous service, Peaks 225°F (107°C)			
Max. Humidity	Resistant to 100% R.H.	DR JJS	Date 28 Sep 07	Dwg No. Q-110031
		CK JH	Date 28 Sep 07	